

**[ SUPERIOR QUALITY  
FINISH ]**

# TX130 FINISHING FILLER

- ▶ **VERY HIGH ADHERENCE**
- ▶ **REINFORCED HARDNESS**
- ▶ **REDUCES PAINT ABSORPTION**
- ▶ **EXTRA FINE AND WHITE**
- ▶ **EASY TO RUB DOWN**



## PURPOSE

Ready to use smoothing surfacer for high quality extra fine finishing, interior use, manual application.

## SUBSTRATES

**TX130** can be applied on:

- Old painted surfaces
- Gypsum plaster
- Plaster tiles
- Plasterboard
- Primed wood
- Cement

## OVERCOATING

**TX130** can be coated over by any type of matt or satin-finish, including epoxies and polyurethane, and wall covering

## Physical and technical FEATURES

**TX130**: filler in paste form for interior use, made of very fine calcium carbonates loads and resins

- Characterization (NFT 36-005): Family III-Class 2
- Codification (EN 16566):  $C_3S_1V_0W_0A_0C_0R_0$
- Application thickness: up to 1 mm per coat
- Consumption: Approx. 200 to 250 g/m<sup>2</sup> on flat substrate such as plasterboard
- Second coat: once the filler is dry
- Overcoat: When fully dry
- Colour: Extra white
- Adhesion filler/substrate (EN 16566): > 0.5 Mpa

## USE AND STORAGE CONDITIONS

- Application tool : With smoothing or surfacing blade
- Tools cleaning: with water
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost and sun.

## PACKAGING

- Bucket of 25 kg

## RECOMMENDATIONS and care for use

- Do not apply under a temperature < 8 °C and > 35 °C nor under an hygrometry rate over 70%.
- Do not apply on overheated surfaces
- Do not apply on damp substrates
- Do not apply on polystyrene, nor on wall paper, nor on exterior substrates.

## SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

## NORMATIVE DOCUMENTS to be referred to

- EN 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204): wall papers and wall coverings processing

## HEALTH AND SAFETY

- No danger tag.
- Very low VOC emissions : < 0,01 %
- Safety data sheets available on [www.toupretpro.co.uk](http://www.toupretpro.co.uk) or [toupret.com](http://toupret.com).

The data sheet information, especially the guidelines relevant to the application and final use of **TX130** are provided in good faith and result from the knowledge of the products and experience of TOUPRET Company. The product is required to be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions



Information on the level of emission of volatile substances in indoor air, presenting a risk of inhalation toxicity, on a class scale from A + (very low emissions) to C (high emissions).