

ALL  
SUBSTRATES

# TX230

## EXTERIOR FINISHING SURFACER

- ▶ IDEAL ON FAÇADES TO BEAUTIFY FINISHING COATINGS
- ▶ ADHERES ON ALL SUBSTRATES EVEN ON TILES
- ▶ EXCELLENT WATER RESISTANT PROPERTIES
- ▶ READY-MIXED



### PURPOSE

Ready to use all substrates finishing surfacer, exterior and interior use, manual application. Recommended externally for façade application and internally in damp rooms (kitchens, bathrooms,...) and in renovation to obliterate ceramic tiles.

### SUBSTRATES

TX230 can be applied on:

- Old painted substrates
- Very smooth and flexible substrates
- Tiles
- Concrete
- Gypsum plaster
- Plasterboard
- Primed wood
- Polystyrene
- Cork
- Drywall lining
- Plastic coverings
- Cement

### OVERCOATING

TX230 can be coated over by any type of paint, excepted polyurethane and sovente-based epoxy paints.

### Physical and technical FEATURES

TX230: a filler in paste form for exterior and interior use, made of mineral and synthetic resin

- Characterization (NFT 36-005): Family IV - Class 4b
- Codification (EN 16566):  $G_3S_2V_0W_0A_0C_0R_5$
- Application thickness: up to 3 mm per coat
- Consumption : 1.7 kg / m<sup>2</sup> / mm
- Second coat: once the filler is dry
- Overcoat: When fully dry
- Colour: Bright beige
- Adhesion filler/substrate EN 16566): > 0.8 Mpa

### USE AND STORAGE CONDITIONS

- Application tool : With trowel or smoothing blade
- Tools cleaning: with water
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost and sun.

### PACKAGING

- Bucket of 25 kg

### RECOMMENDATIONS and care for use

- Do not apply under a temperature < 5 °C and > 35 °C nor under an hygrometry rate over 80%.
- Do not apply on overheated surfaces
- Do not apply on damp substrates
- Before sticking any wall coating on a flexible substrate coated or filled with TX230, wait a minimum of one week for the product to fully dry and harden. Proceed with a preliminary test.
- If necessary, rub down as soon as the filler is dry (TX230 is rich in resin and its hardness increases with time)
- On ceramic tiles, proceed in 2 coats with a thin coat at first to allow quick drying.

### SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- EN 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204): wall papers and wall coverings processing
- DTU 42.1 (NFP 84-404) : Façades renovation with polymer-based waterproofing coatings.

### HEALTH AND SAFETY

- No danger tag.
- Quantity of VOC emissions : < 1 %
- Safety data sheets available on [www.toupretpro.co.uk](http://www.toupretpro.co.uk) or [toupret.com](http://toupret.com).

The data sheet information, especially the guidelines relevant to the application and final use of TX230 are provided in good faith and result from the knowledge of the products and experience of TOUPRET Company. The product is required to be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions