

# WOOD FILLER

## WOOD FILLER

**[READY  
TO USE]**



- ▶ **EASY TO STAIN OR PAINT**
- ▶ **CAN BE DRILLED**
- ▶ **WHITE IN COLOUR**

### PURPOSE

Ready to use **WOOD FILLER**, for interior and exterior use, manual application.

### SUBSTRATE

**WOOD FILLER** applies on any types of woods, including exotic species, chipboard and plywood.

### OVERCOATING

**WOOD FILLER** can be overcoated by any type of conventional paints, varnishes and stains.

### Physical and technical FEATURES

**WOOD FILLER**: is a filler in paste form, for interior or exterior use, made of mineral extracts and selected binders.

- Characterization (NFT 36-005): Family IV class 4b
- Codification (NFT 30-608):  $G_3E_5S_2V_0W_0A_0C_0$
- Application thickness: up to 1 cm
- Second coat: once the filler is dry
- Overcoat: 12 to 24 H average time (after complete drying)
- Colour: cream white
- Adhesion filler/substrate (NFT 30-608): > 0,8 MPa

### USE AND STORAGE CONDITIONS

- Application tools: coating knife, smoothing blade or trowel.
- Tools cleaning : with water.
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost and sun.

### PACKAGING

- Tub of 1.25 kg

### RECOMMENDATIONS and care for use

- Do not apply on Polystyrene, nor on damp substrates.
- Do not apply under a temperature below 5 °C and above 35 °C nor under an hygrometry rate above 80%.
- On exterior substrates **WOOD FILLER** is required to be coated over.
- On rough (unprepared) wood, it is recommended to apply **TOUPRET WOOD HARDENER** beforehand.

### SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- NFT 30-608: Coating fillers for interior works and/or exterior.
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.

### HEALTH AND SAFETY

- No danger tag.
- Very low VOC emissions : < 0,05 %
- Safety data sheets available on <http://www.toupretpro.co.uk> or [toupret.com](http://www.toupret.com).

The data sheet information, especially the guidelines relevant to the application and final use of Le **WOOD FILLER** are provided in good faith and result from the knowledge of the products and experience of **TOUPRET** company.

The product is required to be used as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.